

Wall mounted unit

FTXP-M / FTXP-M9



comfora



Practically inaudible



Energy saving during standby mode



3-D air flow



Online controller via app



Multi model application

Discreet wall mounted unit providing high efficiency and comfort

- › Practically inaudible
- › Online controller (optional)
- › Silver allergen removal and air purifying filter
- › 3-D airflow: air is blown into all corners of a room
- › Ideal for above door installation

- › Bluevolution range: lower environmental impact
- › Seasonal efficiency values up to A++ in cooling and heating
- › Space saving contemporary wall mounted design

FTXP-M9 / FTXP-M + RXP-M



FTXP20-71M9



RXP-M



ARC480A11


Indoor unit		FTXP/FTXP			20M9	25M9	35M9	50M	60M	71M		
Dimensions	Unit	HeightxWidthxDepth			mm			286 x770 x225			295 x990 x263	
Weight	Unit	kg			8.50			9.00			13.5	
Air filter	Type				Removable / washable							
Fan	Air flow rate	Cooling	Silent operation/Low/ Medium/High	m³/min	4.2 /5.6 /7.4 /9.5	4.2 /5.8 /7.7 /9.7	4.5 /6.3 /8.3 /11.5	8.3 /11.5 /14.0 /16.3	9.2 /11.8 /14.4 /16.8	10.1 /11.8 /14.4 /16.8		
		Heating	Silent operation/Low/ Medium/High	m³/min	5.2 /6.2 /8.1 /10.4	5.2 /6.4 /8.1 /10.4	5.3 /7.0 /9.0 /11.5	10.4 /11.8 /14.4 /17.3	11.0 /12.4 /15.3 /17.9			
Sound power level	Cooling	dBA			55		58	59	60	62		
	Heating	dBA			55		58	61	62			
Sound pressure level	Cooling	Silent operation/Low/High	dBA	19 /25 /39	19 /26 /40		20 /27 /43	27 /34 /43	30 /36 /45	32 /37 /46		
	Heating	Silent operation/Low/High/ Super high	dBA	21 /28 /39 /-	21 /28 /40 /-		21 /29 /40 /-	-30 /38 /42	-32 /40 /44	-33 /41 /45		
Control systems	Infrared remote control				ARC480A53							
	Wired remote control				BRC944B2 / BRC073A1							
				-								

Outdoor unit				RXP	20M	25M	35M	50M	60M	71M
Dimensions	Unit	HeightxWidthxDepth		mm	550x658x275			734x870x373		
Weight	Unit			kg	26		28	46.0	50.0	
Sound power level	Cooling			dBA	60		62	61	63	66
	Heating			dBA	61		62	61	63	65
Sound pressure level	Cooling	Nom./High		dBA	-46		-48	47/-	49/-	52/-
	Heating	Nom./High		dBA	-47		-48	49/-		52/-
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-10~48					
	Heating	Ambient	Min.~Max.	°CWB	-15~24					
Refrigerant	Type				R-32					
	GWP				675.0					
	Charge			kg/TCO2Eq	0.55/0.37		0.70/0.48	0.90/0.61	1.15/0.78	
Piping connections	Liquid	OD		mm	6,35			6,4		
	Gas	OD		mm	9,5			12,7		
	Piping length	OU - IU	Max.	m	15			30		
	Additional refrigerant charge			kg/m	0.02 (for piping length exceeding 10m)					
	Level difference	IU - OU	Max.	m	12			20		
Power supply	Phase/Frequency/Voltage			Hz/V	1~/50/220-240					
Current - 50Hz	Maximum fuse amps (MFA)			A	-					

See separate drawing for operation range | See separate drawing for electrical data | Contains fluorinated greenhouse gases

Efficiency data		FTXP + RXP	20M9 + 20M	25M9 + 25M	35M9 + 35M	50M + 50M	60M + 60M	71M + 71M
Cooling capacity	Min./Nom./Max.	kW	1.3/2.00/2.6	1.3/2.50/3.0	1.3/3.50/4.0	1.7/5.0/6.0	1.7/6.0/7.0	2.3/7.1/7.3
Heating capacity	Min./Nom./Max.	kW	1.30/2.50/3.50	1.30/3.00/4.00	1.30/4.00/4.80	1.7/6.0/7.7	1.7/7.0/8.0	2.3/8.2/9.0
Power input	Cooling	Min./Nom./Max.	kW	0.31/0.50/0.72	0.31/0.65/0.72	0.29/1.01/1.30	0.332/1.824/2.980	0.449/2.689/3.274
	Heating	Min./Nom./Max.	kW	0.25/0.52/0.95	0.25/0.69/0.95	0.29/1.00/1.29	0.440/1.579/2.356	0.456/1.928/2.787
Space cooling	Energy efficiency class		A++					
	Capacity	Pdesign	kW	2.00	2.50	3.50	5.0	6.0
	SEER			6.79	6.92	6.62	7.30	6.82
	Annual energy consumption		kWh/a	103	126	186	240	308
Space heating (Average climate)	Energy efficiency class		A++					
	Capacity	Pdesign	kW	2.20	2.40	2.80	4.60	4.80
	SCOP/A			4.65	4.61	4.64	4.40	4.10
	Annual energy consumption		kWh/a	662	728	845	1,463	1,638

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · Oostende (Responsible Editor)



ECPEN22-046



04/2022



Daikin Europe N.V. participates in the Eurovent Certified Performance programme for Liquid Chilling Packages and Hydronic Heat Pumps, Fan Coil Units and Variable Refrigerant Flow systems. Check ongoing validity of certificate: www.eurovent-certification.com

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.